



733 Harbour Way South
 Richmond, CA 94804
 Tel : (510) 965 9494
 Fax: (510) 965 9495
 www.lexfloor.com

Acoustic Sound

Underlayment with Moisture Barrier

Acoustic Sound Laminate Underlay - Provides a superb sound barrier when installed under laminate flooring, engineered wood or hardwood floors.

Acoustic Sound absorbs and reduces the transmission of noise associated with normal foot traffic further enhancing the acoustic ambiance of the space in which it is installed.

PROPERTY	SPECIFICATION
Materials	High Density Rubber
Color	Green
Roll Size	54"x22.22" (100sq.ft.roll)
Density, pcf	44 lbs.
Thickness (in inches) (+/-5% manufacturing tolerance)	0.25mm/0.10
Mold and Mildew Resistant	YES
Anti-Microbial	YES: GUARDIAN
Non-allergenic	YES
Facing-Top	Ployester Foil
Facing-Bottom	Polyester non-woven
Shipping Weight	41 lbs.
Moisture Resistance (ASTM D-1667)	98%
Impact Sound Transmission ASTM-E492-90(ASTM-E989-89)	Class(IIC) = 71
Sound Transmission Loss ASTM E90-02.(ASTM-E413-87)	Class(STC) = 73
"R" Value	3.19 (ft ² - F-hr/Btu - in.)

Acoustic Sound should be installed in accordance with flooring manufacturers published instructions. This product is designed for floating floor glue in, snap in or double glue installation.